

BASWA Drywall Screw

2021 / 1



Product description and application areas

BASWA drywall screw for fastening BASWA DTG acoustic panels and other materials (e.g. plasterboard, etc.) to metal substructures up to 0.7 mm sheet thickness indoors.

Product Specifications

Material	Phosphated case hardened steel
Article number	a 352
Shape	Double thread fine pitch with trumpet head cross recess, needle
Dimensions	TN Ø 3.9 x 55 mm
Consumption per m²	12–15 pcs./m ² (when installing BASWA DTG acoustic panels)
Content	500 pcs./box
Weight	1,7 kg / box à 500 piece
Storage	Store dry

Delivery

Delivery form

Box

Delivery Information

Improper transport can lead to damage. The goods must be protected against mechanical influences and loads.

For further delivery information please contact BASWA acoustic AG, T +41 (0)41 914 02 22.

Legal notice

The above information, in particular the suggestions for the processing and use of our products, are based on our expertise and experience in the normal case, provided that the products have been stored and applied properly. Because of the different materials, surfaces and different working conditions, no guarantee of a work result or a liability, no matter what legal relationship, can be inferred from these notes or from a verbal consultation, unless it can be shown that we have acted with intent or gross negligence. Here, the user must prove that he has provided BASWA with all the information required for a proper and promising assessment by BASWA, on time and in full. The user must test the products for their suitability for the intended purpose. The product specifications are subject to change without notice. The protective rights of third parties must be observed. In addition, our respective terms and conditions of sale and delivery apply. The latest product data sheet, which can be requested from us, applies.